



HP Stitch S1000 126-in Printer

Superwide dye-sub production printing designed to simplify your operation



Beat client expectations with high-quality prints

- Produce high-value jobs with 1200 native dpi, deep black, and vivid colors.
- Get sharp results, even when printing high-density jobs direct-to-fabric, with the Drop & Dry system.
- Reliable image quality with the Smart Nozzle Compensation system and the latest Optical Media Advance Sensor.

Meet deadlines with high productivity

- Easily handle short deadlines and seasonal peaks with production speeds up to 2370 ft²/hr (220 m²/hr).
- Maximize uptime with user-replaceable printheads and HP Service Edge preventive maintenance support.²
- Confidently print unattended with the spreader rollers, 10-liter ink supplies, and rolls up to 600 lb.
- Control your print operations anytime, anywhere and make data-driven decisions with HP PrintOS.³

Save time with easy operation¹

- In 40% less time, a single operator can easily load and unload both transfer paper and textile rolls.¹
- Reduce daily manual interventions with fully automated printhead maintenance.
- Confidently distribute jobs across the fleet with best-in-class color consistency¹ and HP SmartColor tools.
- Get accurate colors over time, even as environmental conditions change, with the built-in spectrophotometer.

For more information, please visit <http://www.hp.com/go/stitches1000>

Dynamic security enabled printer. Only intended to be used with cartridges using an HP original chip. Cartridges using a non-HP chip may not work, and those that work today may not work in the future. More at: <http://www.hp.com/go/learnaboutsupplies>

¹ Compared to alternative 126-inch dye-sublimation based textile printers under \$250,000 USD available as of February, 2019. 40% less time based on internal HP testing in February, 2019 and features including automatic media tension adjustment and easy, simple media path. Only the HP Stitch S Printer series provides HP SmartColor tools and a built-in spectrophotometer for a better color management experience.

² End-to-end service experience managed by HP. Individual services may be provided by HP or an HP-authorized partner. Some services depend on printer, service contract, and region availability.

³ The HP PrintOS Mobile Application is compatible with Android™ 4.0 or later and iPhone mobile devices running iOS 8 or later and requires the printer and the smart phone to be connected to the Internet.

Technical specifications

Print

Printing modes	350 m ² /hr - Max Speed (1-pass) 220 m ² /hr - Production Economy (2-pass) 160 m ² /hr - Production Fast (3-pass) 130 m ² /hr - Production Quality (4-pass) 100 m ² /hr - High Quality (6-pass) 3770 ft ² /hr - Maximum Speed (1-pass) 2370 ft ² /hr - Production Economy (2-pass) 1720 ft ² /hr - Production Fast (3-pass) 1400 ft ² /hr - Production Quality (4-pass) 1080 ft ² /hr - High Quality (6-pass) 1 and 2 pass are available for transfer printing only
----------------	--

Print resolution	Up to 1200 x 600 dpi
------------------	----------------------

Ink types	HP Dye Sub Inks
-----------	-----------------

Ink cartridges	4 HP Thermal Inkjet (cyan, magenta, yellow, black)
----------------	--

Cartridge size	10 L
----------------	------

Printheads	4 (2 black/cyan, 2 magenta/yellow)
------------	------------------------------------

Long-term print-to-print repeatability	Average ≤ 1 dE2000, 95% of colors ≤ 1.5 dE2000 ¹
--	---

Media

Handling	Roll-to-roll, ink collector
----------	-----------------------------

Media types	Sublimation transfer papers, sublimation polyester fabrics
-------------	--

Roll size	635 to 3200 mm (25 to 126 in)
-----------	-------------------------------

Roll weight	300 kg (Up to 660 lb (126-in roll)); Up to 220 lb (63-in roll)
-------------	--

Roll diameter	35 cm (13.8 in)
---------------	-----------------

Thickness	Up to 0.5mm (Up to 19.7 mil)
-----------	------------------------------

Applications	Banners; Billboards; Displays; Exhibition and event graphics; Exterior signage; Interior decoration; POP/POS; Textile
--------------	---

Connectivity

Interfaces	Gigabit Ethernet (1000Base-T)
------------	-------------------------------

Dimensions (w x d x h)

Printer	574 x 138 x 167 cm (228 x 54 x 66 in)
---------	---------------------------------------

Shipping	586 x 181 x 191 cm (231 x 71 x 75 in)
----------	---------------------------------------

Operating area	8.7 x 4.3 m (344 x 168 in)
----------------	----------------------------

Weight

Printer	1300 kg (2866 lb)
---------	-------------------

Shipping	1945 kg (4288 lb)
----------	-------------------

What's in the box

HP Stitch S1000 126-in Printer, printheads, printhead cleaning kit, 126-in spindles (x2), spreader rollers, ink collector, set of ink collector foams and filters, aerosol extractor channel, HP Internal Print Server and monitor, documentation software, user manual, media edge holders (x4), cleaning supplies, pneumatic gun, beacon

Environmental ranges

Operating temperature	15 to 30°C (59 to 86°F)
-----------------------	-------------------------

Operating humidity	20 to 70% RH (non-condensing)
--------------------	-------------------------------

Acoustics

Sound pressure	< 64 dB(A) (operating); < 52 dB(A) (idle);
----------------	--

Power

Consumption	6 kW (typical)
-------------	----------------

Certification

Safety	IEC 60950-1+A1+A2 compliant; United States and Canada (CSA listed); EU (LVD and MD compliant, EN60950-1, EN12100-1, EN60204-1, and EN1010); Russia, Belarus and Kazakhstan (EAC); Australia, New Zealand (RCM)
--------	--

Electromagnetic	Compliant with Class A requirements, including: USA (FCC rules), Canada (ICES), EU (EMC Directive), Australia (ACMA), New Zealand (RSM)
-----------------	---

Environmental	WEEE; EU RoHS; China RoHS; REACH; CE marking compliant
---------------	--

Warranty	One-year limited hardware warranty
----------	------------------------------------

Ordering information

Product

4DC17A	HP Stitch S1000 126-in Printer
--------	--------------------------------

Accessories

4TA09A	HP Stitch S1000 Ink Collector Foam Kit
7JC63A	HP Ergosoft Pro RIP S1000 Color Edition
CZ059A	HP Series 1000/3000 126-in Carbon Fiber Spindle
D9Z41B	HP Large Format Onyx Thrive RIP Software
L5E74C	HP Large Format Caldera Grand RIP Software

Original HP printing supplies

4UV63A	HP 638 10-liter Black Stitch Dye Sublimation Ink Cartridge
4UV64A	HP 638 10-liter Cyan Stitch Dye Sublimation Ink Cartridge
4UV65A	HP 638 10-liter Magenta Stitch Dye Sublimation Ink Cartridge
4UV66A	HP 638 10-liter Yellow Stitch Dye Sublimation Ink Cartridge
4UV67A	HP 618 Magenta and Yellow Stitch Dye Sublimation Printhead
4UV68A	HP 618 Black and Cyan Stitch Dye Sublimation Printhead
4UV69A	HP 618 Stitch Dye Sublimation Printhead Cleaning Kit
5ZS55A	HP 638B 10-liter Black Stitch Dye Sublimation Ink Cartridge
5ZS56A	HP 638B 10-liter Cyan Stitch Dye Sublimation Ink Cartridge
5ZS58A	HP 638B 10-liter Magenta Stitch Dye Sublimation Ink Cartridge
5ZS59A	HP 638B 10-liter Yellow Stitch Dye Sublimation Ink Cartridge

ECO highlights

- ECO PASSPORT certified dye sublimation inks¹
- Free, convenient HP ink cartridge and printhead recycling²

Please recycle large-format printing hardware and printing supplies. Find out how at our website hp.com/ecosolutions

¹ Original HP Dye Sublimation Inks for the HP Stitch S Printer series are certified ECO PASSPORT by Oeko-Tex,® which is a globally uniform testing and certification system for textile chemicals, colorants, and auxiliaries. It consists of a two-step verification procedure that analyzes whether the compounds and each ingredient meet specific criteria for sustainability, safety, and regulatory compliance.

² Program availability varies. Please check <http://www.hp.com/recycle> for details.

¹ The color variation inside a printed job has been measured at 4-pass mode on transfer media and also in direct-to-fabric situations within this limit: maximum color difference (95% of colors) ≤ 1.5 dE2000. Reflective measurements on a 943 color target under CIE standard illuminant D50, and according to the standard CIEDE2000 as per CIE Draft Standard DS 014-6/E:2012. 5% of colors may experience variations above 1.5 dE2000. Backlit substrates measured in transmission mode may yield different results. Results are dependent on sublimation process variability.

